

DECLARATION OF PERFORMANCE



DOP Polyflor XLPU

1. Unique identification code of the product-type:

PFXLPU-DoP

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Polyflor XLPU (EN ISO 10581 Homogeneous Vinyl Floorcovering)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

James Halstead PLC, Beechfield, Hollinhurst Road, Radcliffe, Manchester, M26 1JN, United Kingdom

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

James Halstead PLC, Beechfield, Hollinhurst Road, Radcliffe, Manchester, M26 1JN, United Kingdom

S. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

In case of the declaration of performance concerning a construction product covered by a harmonised standard:
Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).

British Textile Technology Group (BTTG) Wira House, West Park Road, Leeds, LS16 6QL.

Notified Body 0338

not applicable

certificate of constancy of performance

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

9.	Declared performance
	Facantial

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	B _{II} -s1	EN 14041: 2004/AC:2006
Content of Pentachlorophenol	° DL PCP	EN 14041: 2004/AC:2006
Formaldehyd Emissions	° NA HCHO	EN 14041: 2004/AC:2006
Slip resistance	DS	EN 14041: 2004/AC:2006
Electrical behavior (dissipative)	NPD	EN 14041: 2004/AC:2006
Electrical behavior (conductive)	NPD	EN 14041: 2004/AC:2006
Electrical behavior (antistatic)	NPD	EN 14041: 2004/AC:2006
Thermal conductivity [W/mK]	0.25 W/m.K	EN 14041: 2004/AC:2006
Water-tightness	NPD	EN 14041: 2004/AC:2006

10.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point s
	This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4
	Signed for and on behalf of the manufacturer by:

Mike Minett, Quality Manager

(name and function)

6th January 2017, Manchester, UK

(place and date of issue)

M G Minett

(signature)